



360° vision for mobile robots

3D camera-based perception platform

- Obstacle avoidance and clear space detection for route planning of autonomous vehicles
- Also detects objects below and above the scanning plane of a safety scanner
- 3D PMD cameras detect even difficult scenes and objects, e.g. forks
- Powerful integrated image evaluation, output of zone evaluation and occupancy grid

ifm – close to you!



ToF

Video Processing Unit			
Description			Order no.
Video Processing Unit (VPU) Connection for up to 6 cameras, Gigabit Ethernet interface for sensor signals			OVP811
Camera heads			
Dimensions [mm]	Image resolution [pixel]	Angle of aperture [°]	Order no.
90 x 31 x 26	38 K	60 x 45	O3R222
90 x 31 x 26	38 K	105 x 78	O3R225

3D obstacle detection


Autonomous transport systems have to overcome two major challenges: on the one hand, collision avoidance with objects and persons, on the other hand, autonomous avoidance of obstacles. The frequently used safety scanners are only of limited help here, as they only detect the travel path in a plane just above the ground. This is where the camera platform shows its advantage: it processes the signals from up to six 3D PMD cameras installed all around the vehicle and evaluates the environment three-dimensionally, i.e. both the ground area below the field of view of the safety scanners (e.g. holes in the ground) and the view diagonally upwards. In this way, hanging loads such as crane hooks, for example, are also detected. Powerful algorithms ensure that false detections are virtually eliminated despite the high detection rate.



The robotics platform captures the situation in a 2D image and in 3D distance data.

Easy integration

The user can define zones in the form of segmented polygons in which the system evaluates the occupancy and provides the vehicle's steering system with clear data for safe and collision-free driving.



The obstacle in front of the vehicle is projected in a map on the ground. One of the three zones or the area in the so-called occupancy grid is then output as occupied.

BEST FRIENDS

We reserve the right to make technical alterations without prior notice. · 09.2023
ifm electronic gmbh · Friedrichstr. 1 · 45128 Essen



Graphic display
Programmable HMI for the control of mobile machines



Multiturn encoders
Precise detection of positions and rotational movement



ecomatController
Powerful 32-bit controllers reliably control AGVs



For further technical details, please visit:
ifm.com/fs/OVP811